

## Telehandler / Zoom Boom

Used Telehandler Seattle - Telehandlers go by many different names including a boom lift, telescopic handler, Cherry picker or teleporter. This industrial equipment is commonly used in a variety of industries including agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. The operator can utilize a variety of attachments at the end of the articulating boom to complete different jobs. Different attachments such as a bucket, pallet forks, a muck grab or a winch can help the machine complete many jobs. The pallet forks are the most popular telehandler attachment. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. These machines enable cargo pallets to be unloaded and loaded from a trailer and placed on rooftops, racking or other high and hard to access locations. Normally, high rooftop applications would require the use of a crane; however, telehandlers can complete this task more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Moving items from unreachable locations that cannot be completed with a backhoe loader or wheeled loader give telehandlers a huge advantage. Telehandlers can directly access trailer units with high sides, hoppers or applications that would typically need a conveyor or loading ramp. Using one machine to finish numerous jobs saves storage space, money and time. Telehandler machines can work in conjunction with a crane jib. Various attachments may be used including rotators, dirt buckets, grain buckets and power booms. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. However, the main advantage of the telehandler is additionally its' largest limitation. The boom acts as a lever when it extends or raises with heavy loads. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. If the machine works as a single boom loader instead of using twin arms while carrying a large load, there is a chance that weakness can occur even in the most carefully designed units. A machine with a 5K lb. capacity could safely lift 400 lbs. while fully extended using a retracted low boom angle. The same piece of equipment with a five thousand pound lift capacity and retracted boom may be capable as supporting up to ten thousand pounds once the boom is raised to seventy degrees. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Updated telehandler models have computers and sensors. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A stabilizing rotary joint between the upper and lower frames may be called a mobile crane that can use a bucket. There are many models of telehandlers differing in size, weight, boom designs and reach. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. A low pivot boom ensures better operator visibility for transporting loads on compact units. Obviously, the compact telehandler has narrower and tinier dimensions. The compact units offer a reach capacity between thirteen to twenty feet and a lifting capacity ranging from five thousand to seven thousand pounds. The versatility of the compact telehandler makes it popular in a variety of applications. It may be used as a tool carrier or a pick and place machine. It is commonly utilized in spaces that are tight and cramped. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. Telehandlers can enter internal building access in hard-to-reach locations. Compact telehandlers are commonly used in nurseries, landscaping, multi-story construction, building strip malls and garages, masonry, erecting steel and more. Farming and agri-business applications often rely on telehandlers to accomplish many tasks. Telehandlers can be found with two and four-wheel

drive and crab steering capabilities. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. The 4-WD units are capable of having a tighter turning radius and can travel difficult terrain. Crab steering is responsible for the increased maneuverability, allowing the front and rear wheels to shift forty-five degrees to the right or left. There are a variety of cab interior options available for compact telehandlers. On the lower-end models, a rollover protective cage structure is in place for safety. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. Operators enjoy spacious accommodation for ultimate comfort. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Different high-flow auxiliary hydraulics and high-pressure hydraulics run the variety of attachments. These attachments increase the functions the machine is capable of. Compact units are more commonly utilized for ground engaging jobs. Adding a bucket attachment can make a compact telehandler transform into a mini excavator. There are popular attachments including brooms for sweeping, truss booms for extended reach, side-shifting and rotating fork carriages, heavy and light-duty buckets, augers for planting trees or digging holes and many items. Skid steer attachments are being manufactured for certain compact telehandler designs for even more versatility.